



GCO - FT - 026	
RV 1	SEP/09



Baterías, estacionarias de Plomo (AGM), selladas con válvula auto-regulada (VRLA)

SPECTRONIC

CARACTERISTICAS

Marca	Referencia	Tipo	Voltaje Nominal (VDC)	Capacidad Amp/h	Tipo de Terminal	Largo (mm)	Ancho (mm)	Alto total (mm)	Peso (kg)
Fulibattery	FL640GS	VRLA	6	4	F1	70	47	107	0,72
Fulibattery	FL1250GS	VRLA	12	5	F1	90	70	107	1,75
Fulibattery	FL1275HR	VRLA	12	7.5	F1	151	65	101	2,32
Fulibattery	FL1290HR	VRLA	12	9	F1	151	65	101	2,7
Fulibattery	FL12120GS	VRLA	12	12	F1	151	98	101	3,8
Fulibattery	FL12180GS	VRLA	12	18	I - M5	181	77	167	5,5
Fulibattery	FL12260GS	VRLA	12	26	I - M5	166	175	125	8,1
Fulibattery	FL12350GS	VRLA	12	35	I - M6	195	130	164	11,2
Fulibattery	FL12400GS	VRLA	12	40	I - M6	197	165	170	12,97
Fulibattery	FL12550GS	VRLA	12	55	I - M6	230	138	213	18
Fulibattery	FL12800GS	VRLA	12	80	I - M6	258	169	212	21,7
Fulibattery	FL12900GS	VRLA	12	90	I - M6	306	169	213	26,7
Fulibattery	FL12900GS	VRLA	12	100	I - M8	330	172	222	31,5

**GARANTIA
12 MESES**



SPECTRONIC LTDA
 CARRERA 14 No. 98-31 PBX. 623 00 55 FAX. 256 01 99 BOGOTA COLOMBIA
 www.spectronic.com.co / E-Mail: servicio@spectronic.com.co

